

# TJ625HD6 (208 VAC)

## Diesel Generator






### Output Power

|                     |     |     |
|---------------------|-----|-----|
| Standby Power (ESP) | kVA | 625 |
|                     | kW  | 500 |
| Prime Power (PRP)   | kVA | 567 |
|                     | kW  | 454 |

### Size

|           | W x L x H<br>(mm)  | Weight<br>(kg) | Fuel Tank<br>(lt) | Noise dB(A)<br>@ 7m |
|-----------|--------------------|----------------|-------------------|---------------------|
| Canopied  | 1684x5360x2515     | 4503           | 970               | 87                  |
| Open Skid | 1650 x 3500 x 1970 | 3352           | 970               | N/A                 |



### Continuous Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

### Standby Power

The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 hrs of operation per year under average of 70% load. Overloading isn't permissible.

### Prime Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

TTDTJ625HD620251216EN

### Engine

|                                    |        |                         |
|------------------------------------|--------|-------------------------|
| Manufacturer                       |        | HYUNDAI                 |
| Model                              |        | DP158LD                 |
| Cylinder Configuration             |        | V TYPE                  |
| No of Cylinders                    |        | 8                       |
| Displacement                       | lt     | 14,6                    |
| Stroke                             | mm     | 142                     |
| Bore                               | mm     | 128                     |
| Compression Ratio                  |        | 15:01                   |
| Aspiration                         |        | TURBOCHARGE-INTERCOOLER |
| Governor Type                      |        | ELECTRONIC              |
| Cooling System                     |        | WATER                   |
| Coolant Capacity                   | lt     | 79                      |
| Lubrication Oil Capacity           | lt     | 22                      |
| Electrical System                  | VDC    | 24                      |
| Speed / Frequency 60 Hz            | Hz     | 1800 rpm / 60 Hz        |
| Engine Gross Power (Standby 60 Hz) | kW     | 556                     |
| Fuel Consumption %110 ESP 60 Hz    | lt/h   | 139,6                   |
| Fuel Consumption %100 PRP 60 Hz    | lt/h   | 127,1                   |
| Fuel Consumption %75 PRP 60 Hz     | lt/h   | 92,9                    |
| Fuel Consumption %50 PRP 60 Hz     | lt/h   | 62,3                    |
| Exhaust Outlet Temperature 60 Hz   | °C     | 567                     |
| Exhaust Gas Flow 60 Hz             | m3/min | 108                     |
| Combustion Air Flow 60 Hz          | m3/min | 36,6                    |
| Cooling Air Flow 60 Hz             | m3/min | 850                     |

### Alternator

|                      |  |                                                 |
|----------------------|--|-------------------------------------------------|
| No of Phases         |  | 3                                               |
| Power Factor         |  | 0,8                                             |
| No of Bearings       |  | SINGLE                                          |
| No of Poles          |  | 4                                               |
| No of Leads          |  | 6-12                                            |
| Insulation Class     |  | H-F                                             |
| Degree of Protection |  | IP 23                                           |
| Excitation System    |  | AVR (Automatic Voltage Regulator),<br>Brushless |

### Standard Equipments

#### Engine

In Teksan generator sets, leading engine brands that have state of the art technology and have compliance with ISO 8528, ISO 3046, BS 5514, DIN 6271 standards, are being used. These engines with low fuel consumption, provide accurate speed setting and order, mount to the fuel pump, also have mechanic or electronic type governors.

#### Alternator

In products Teksan produced, leading alternator brands of the world that have state of the art technology, high quality, productivity and durability, are being used. All alternators, which pass necessary test process and found appropriate according to EC 60034-1; CEI EN 60034-1; BS 4999-5000; VDE 0530, NF 51-100,111; OVE M-10, NEMA MG 1.22. standards, have bearing system that does not need maintenance, with electronic type voltage regulator providing voltage setting.

#### Control Panel

Standard control panel, that is used in Teksan generator sets, ensures comfortable and safe usage. All measured and statistical parameters, operating modes, notice and alarms and condition of generator, are monitored easily from the control panel. On the front of the panel's metal body has electronic control module and the emergency stop button and the panel's metal body is made of steel sheet and is painted with electrostatic powder paint. Teksan offers panel design and solutions that comply with special requirements of customers as well as quality standard panels.

#### Chassis and Fuel Tank

Chassis is manufactured from steel that has features and durability for carrying burden of generator set. Thanks to its rigid structural design and anti-vibration mounts, it reduces vibration level to minimum. All chassis contain lifting lugs. Apart from chassis that are produce by Teksan, special solutions that design in accordance with customer desires, make transportation and positioning easier. In generator sets with 1375 kVA power, the fuel tank is located inside the chassis. For models of 1375 kVA and above, the fuel tank is usually external, but in some cases, it can also be located inside chassis.

#### Cooling System

System, that consists of quality industrial - type radiator, expansion tank and cooler fan, keeps the temprature of generator set's equipments constant at a proper level.



### Canopy Features

**TEKSAN** Standard Canopies' default features are as follows;

- Compatible with 2000/14/EC directives, certified noise emission level,
- 2 or 4 points transport possibility according to cabin size,
- Hidden exhaust inside the canopy,
- Emergency stop button located on the canopy,
- Improved air suction channel to ensure homogenous cooling in the canopy,
- Radiator air outlet and exhaust with designed towards above,
- Lid on cab that provides to be filled up water and antifreeze easily to the radiator,
- Amplified paint system against corrosion and rust,
- Improved performance in terms of sound insulation,
- Demounted parts that make transportation and maintenance easier,

As well as the standard range of canopies, TEKSAN can also design tailormade canopies with specific sound level or size upon customer requests.

### Optional Equipments

Some Optional Equipments that Teksan provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems,
- The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Trailer,
- Remote monitoring,
- External Fuel Tank

### Control Panel Features-DSE-7320

- 4-Line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Tier 4 CAN engine support
- Integral PLC editor
- Easy access diagnostic page
- CAN and Magnetic Pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on compatible CAN engines)
- Manual fuel pump control
- Engine exerciser
- "Protections disabled" feature
- kW & kV Ar protection
- Reverse power (kW & kV Ar) LED and LCD alarm indication
- Power monitoring (kW h, kV Ar, kV A h, kV Ar h)
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer (DSE7320)
- Unbalanced load protection
- Independent Earth Fault trip
- True dual mutual standby with load balancing timer (DSE7310 only)
- USB connectivity
- Backed up real time clock
- Fully configurable via DSE Configuration Suite PC software
- Configurable display languages
- Remote SCADA monitoring via DSE Configuration Suite PC software
- User selectable RS232 and RS485 communications
- Configurable Gencomm pages
- Advanced SMS messaging (additional external modem required)
- Start & stop capability via SMS messaging
- Additional display screens to help with modem diagnostics
- Idle control for starting & stopping.
- DSENet® expansion compatible
- Heated display option available



### Functions

- AMF unit
- Remote start controller
- Manual start controller
- Engine controller
- Remote display & control unit
- CTs at genset or load side

### Communications

- Web monitoring
- GSM-SMS (required externally modem)
- e-mail
- USB Device
- RS-232
- J1939-CANBUS

### Connection Topologies

- 2 phase 3 wires, L1-L2
- 2 phase 3 wires, L1-L3
- 3 phase 3 wires
- 3 phase 4 wires, star
- 3 phase 4 wires, delta
- 1 phase 2 wires

- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 600341, BS 4999-5000, VDE 0530 standards.
- Producing with ISO9001, ISO14001, ISO 45001, TSE, CE standards.
- All information given in this leaflet is intended for general purposes only.
- Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Asked TBD: To Be Determined NA: Not Available N/A: Not Applicable TTDTJ625HD620251216EN